

#1011

Ready Mixed Emulsion Paints
Version: Revised Date of Issue: 18/07/2012

1. IDENTIFICATION OF PREPARATION

| 61121 - Terrashine Satin | 61122 - Terrashine Eggshell |
|--|---|
| 61125 - Terrashine Super High Gloss | 61126 - Terrashine Super Eggshell |
| 61210 - Terrashield | 61210 - Acrylic Topcoat |
| 61214 - Terrashield Super | 61216 - Maxishield |
| 61221 - Equalising Colour Wash | 61223 - Terracoat Stain |
| 61781 - Flexishield HC | 61810 - Tileshield Standard |
| 61790 - Flexicryl | 62120 - Terralast |
| 62131 - Ipekcy Topcoat | 62136 - Terragene |
| 62150 - Plastic Emulsion | 62180 - Form Plastic |
| 62196 - Ecopaint | 62210 - Soften Saten |
| 62213 - Deccosil | 62214 - Nanogene Silk |
| 62220 - Terratop Silk | 62221 - Ipekcy Basecoat |
| 62223 - Terratop Matt | 62224 - Terratop High Sheen |
| 62230 - Fresco | 62389 - Armoni |
| 67115 - Flexipave Ready Mixed | 67120 - Flexipave Coating Textured |
| 67150 - DiamondCoat Mid-Sheen | 67151 - DiamondCoat Matt |
| Mixture of acrylic/vinyl emulsions, pigments, mineral fillers and additives. | |
| Blend | |
| | |
| | 61125 - Terrashine Super High Gloss 61210 - Terrashield 61214 - Terrashield Super 61221 - Equalising Colour Wash 61781 - Flexishield HC 61790 - Flexicryl 62131 - Ipekcy Topcoat 62150 - Plastic Emulsion 62196 - Ecopaint 62213 - Deccosil 62220 - Terratop Silk 62223 - Terratop Matt 62230 - Fresco 67115 - Flexipave Ready Mixed 67150 - DiamondCoat Mid-Sheen Mixture of acrylic/ vinyl emulsions, pig |

CHINA:

Terraco Architectural Coatings China Co., Ltd.

Tel: +86 (0)20 8759 4742 Fax: +86 (0)20 8526 8056 E-mail: sales@terraco.com.cn Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 621020 48 / 18 Fax: +86 (0)21 625205 47 Email: sales@terraco.com.cn Web: www.terraco.com.cn

EGYPT:

Terraco Egypt Chemical Industries S.A.E.

Tel: +20 (0)22 29184 53 / 57 / 58 Fax: +20 (0)22 29184 80 E-mail: terraco@terraco.com.eg Web: www.terraco.com.eg

JORDAN:

Jordan Swedish Polymers Industrial Corp.

Tel: +962 (0)6 553 8751 Fax: +962 (0)6 553 6560 E-mail: terraco@nol.com.jo Web: www.terraco.jo

IRELAND:

Terraco Technical Centre, Ireland

Tel: +353 (0) 404 66555 Fax: +353 (0) 404 66654 E-mail: technical-centre@terraco.com Web: www.terraco.com

PAKISTAN:

Terraco Pakistan Pvt. Ltd.

Tel: +92 (0)42 3529 70 56-8 Fax: +92 (0)42 3529 70 55 Email: terraco@terraco.pk Web: www.terraco.com

ROMANIA:

Terraco Romania SRL

Tel: +40 (0)749 203 133 Fax: +40 (0)318 148 810 E-mail: ahaque@terraco.com Web: www.terraco.com

RUSSIA:

OOO Terraco Sweden Ltd, Russia

Tel: +7 (0)495 9212 237 Fax: +7 (0)495 6273 881 E-mail: adm@terraco.ru Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563 Fax: +7 (0)4212 410591

E-mail: terracovostok@terraco.khn.ru Web: www.terraco.com

SOUTH KOREA:

Terraco Korea Co., Ltd

Tel: +82 (0) 2 5611 551 Fax: +82 (0)2 5671 771 E-mail: terraco@terraco.co.kr Web: www.terraco.co.kr

THAILAND:

Terraco Industry (Thailand) Limited

Tel: +66 (0)2 946 68 56 / 58 Fax: +66 (0)2 946 68 59 E-mail: terraco@terraco.co.th Web: www.terraco.com

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS

Tel: +90 (0)222 236 0423 Fax: +90 (0)222 236 0425 E-mail: terraco@terraco.com.tr Web: www.terraco.com.tr

UAE:

Terraco UAE Ltd

Tel: +971 (0)4 326 2699 Fax: +971 (0)4 326 2733 E-mail: terraco@terraco.ae Web: www.terraco.com

UK:

ADDAGRIP

Tel: +44 (0)1825 761 333 Fax: +44 (0)1825 768 566 E-mail: sales@addagrip.co.uk Web: www.addagrip.co.uk / www,terraco.com

VIETNAM:

Terraco Vietnam Co., Ltd

Tel: +84 (0)650 3 820 100 Fax: +84 (0)650 3 820101 E-mail: terraco@terraco.com.vn Web: www.terraco.com



#1011

Ready Mixed Emulsion Paints

| 2 | COMPOSITION/ | INFORMATION ON | INGREDIENTS |
|---|--------------|----------------|----------------------|
| | | | 1 II (OILEDIEI 1 I S |

| Chemical Name | Amount | CAS Number |
|------------------------|--------|-------------|
| Water: | >25.0% | 7732-18-5 |
| Acrylic/Vinyl Polymer: | <25.0% | Proprietary |
| Calcium Carbonate: | <50.0% | 1317-65-3 |
| Titanium Dioxide: | <25.0% | 13463-67-7 |
| China Clay: | <15.0% | 1332-58-7 |

3. HAZARDS IDENTIFICATION

| Not classified as dangerous for supply. Avoid inhalation of dust during mixing. | | |
|---|--|--|
| Potential Health Effects | | |
| Eye Contact may cause irritation. | | |
| Skin Prolonged contact may dry the skin resulting in irritation and dermatitis. | | |
| Inhalation Avoid inhalation if product atomised during application, may cause respirate tract irritation. | | |
| Ingestion Ingestion is not considered a potential route of exposure. | | |

| 4. F | IRST | AID | MEASURES |
|------|-------------|-----|-----------------|
|------|-------------|-----|-----------------|

| General | In all cases of doubt or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. | |
|--------------|---|--|
| Eye Contact | Flush eye with water for 15 minutes, holding eye lids apart. Get medical attention if irritation develops. | |
| Skin Contact | Remove contaminated clothing. Wash skin with soap and water or a proprietary skin cleaner. | |
| Inhalation | If exposed to excess levels of dust remove to fresh air. | |
| Ingestion | If accidentally swallowed, obtain immediate medical attention. Show this safety data sheet. Do not induce vomiting. If conscious give milk or water to drink. | |

5. FIRE FIGHTING MEASURES

| Flammable Properties | C.O.C. Flash Point: | None | |
|----------------------------|--|------|--|
| | T.C.C. Flash Point: | None | |
| | Auto ignition temperature: | None | |
| Flammable Limits In Air | L.E.L. | None | |
| | U.E.L. None | | |
| Extinguishing Media | Recommended: Alcohol resistant foam, CO2, Powder, Water spray mist. | | |
| Fire and Explosion Hazards | During a fire, acrylic monomers may be generated at elevated temperatures. | | |
| | If engulfed by ongoing fire do not allow fire fighting run off to enter drains or watercourses. As in any fire wear self-contained breathing apparatus, pressure demand MSHA/NIOSH (approved or equivalent) and full protective gear. | | |



#1011

Ready Mixed Emulsion Paints

| 6. ACCIDENTAL RELEASE MEASURES | | |
|--------------------------------|---|--|
| Safeguards (Personnel) | Exclude all non-essential personnel. Wear appropriate personal protective equipment. | |
| Initial Containment | Absorb spills with inert material, allow to solidify and scrape up. Do not allow to enter drains or watercourses, clean preferably with a detergent. Do not use solvents. | |
| | If the product accidentally enters, rivers, lakes, drains or sewers, the Local Authority should be contacted immediately. | |

| 7. HANDLING AND STORAGE | | | |
|------------------------------------|---|--|--|
| General | Smoking, Eating and Drinking should be prohibited in areas of storage or use. Never use pressure to empty the container. Good housekeeping and regular safe removal of waste materials are recommended. | | |
| Recommended Storage Temperature | Minimum: 5C (41F) Maximum: 35C (95F) | | |
| Shelf Life | 12 months in original sealed containers. | | |
| Storage Precautions | Avoid extremes of temperature. Keep out of reach of children. Store separately from Oxidising Agents, and strongly acidic or alkaline materials. | | |

| 8. EXPOSURE CONTROL | S/PERSONAL PROTECTION | |
|------------------------|--|---|
| Exposure Limits | | No information presently available. |
| | | If user operations generate dust, fumes or mist, use local exhaust ventilation and good general extraction. |
| Personal Protection | | |
| Respiratory Protection | Should not be necessary under normal conditions of use. However suitable respiratory protective equipment should be worn during spray application. | |
| Skin Protection | For brief contact normal work attire should be sufficient. For anticipated prolonged contact, barrier creams should be applied before work is commenced. Suitable gloves should be worn. | |
| Eye Protection | Splashes in eyes may cause irritation; it is recommended that goggles designed to protect against liquid splashes should be worn. | |

Form Medium viscosity paste Odour Slight acrylic odour Boiling Point 100 C Solubility In Water Dispersible Specific Gravity 1.15-1.55 (Water = 1) pH 8-9 Volatile Organic Compounds < 150 gm./ lt.



#1011

Ready Mixed Emulsion Paints

| ľ | ın | STARII | ITV | VND | REAC | TIVITY |
|---|-----|----------|-----|-----|------|--------|
| ı | IU. | 3 I ADII | | AND | NEAU | |

| Stability Stable. | |
|---|--|
| Polymerisation Product will not undergo polymerisation. | |
| Incompatibility With Other Material | Incompatible with oxidising agents and strongly acidic and alkaline materials. |
| Decomposition | May produce acrylic monomers and oxides of carbon on decomposition. |

11. TOXICOLOGICAL INFORMATION

There is no data available on the products themselves.

Repeated or prolonged contact may lead to removal of natural fats from the skin, resulting in non-allergic dermatitis and absorption through the skin.

The products contain small amounts of biocides, not present in quantities sufficient to induce sensitisation by skin contact, but which could elicit an allergic reaction in an already sensitised person.

Splashes in eyes may cause irritation and reversible local damage.

Ingestion may result in sore throat, abdominal pain or nausea.

12. ECOLOGICAL INFORMATION

There is no data available on the products themselves. They should not be allowed to enter drains or watercourses.

13. DISPOSAL CONSIDERATIONS

Do not allow to enter drains and watercourses or anywhere that may affect ground or surface waters. Wastes including emptied containers should be disposed of in accordance with the regulations of the Local Authority.

14. TRANSPORT INFORMATION

To transport within the user's premises, always use closed containers that are secure and upright. Ensure that operational personnel know what to do in event of spillage.

| D.O.T. SHIPPING NAME: | Not Applicable |
|------------------------------------|----------------|
| D.O.T. HAZARD CLASS: | Non-Hazardous |
| IATA HAZARD CLASS/PACKAGING GROUP: | Not regulated |

15. REGULATORY INFORMATION

The products are determined as not being dangerous for supply according to current Chemicals Hazard Information and Packing Regulations in force.

The information contained in this Material Safety Data Sheet, does not substitute the user's own responsibility to carry out an assessment of work place risks as may be required by Health and Safety Legislation.

16. OTHER INFORMATION

The products should not be used for purposes other than those shown on the manufacturer's product labels and technical data sheets. As the specific conditions of use are outside the supplier's control; the user is responsible for ensuring compliance with the relevant legislation in the territory of use.

The information contained in this Material Safety Data Sheet, is based on the current state of knowledge and current state of Legislation. It provides guidance on Health Safety and Environmental aspects of the products, and should not be taken as a guarantee of technical performance or suitability for particular applications.



#1011

Ready Mixed Emulsion Paints

| Approved by: | J. Carey - Group Technical Director. | |
|----------------|--------------------------------------|--|
| Approval date: | 18/07/2012 | |
| Supersedes: | 30/01/2012 | |
| Number: | MSDS No. 1011 | |

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of TERRACO's knowledge. The data on this sheet are related only to the specific materials designated herein. TERRACO assumes no legal responsibility for use or reliance upon this data.